

The Atlas Copco logo is located in the top right corner of the page. It consists of the brand name "Atlas Copco" in a white, italicized serif font, centered between two horizontal white bars. The background of the entire page is a photograph of a warehouse or factory floor. In the foreground, a yellow Jungheinrich forklift is visible, with a worker in a high-visibility vest operating it. The forklift is carrying a wooden pallet loaded with several large blue industrial drums. In the background, there are high industrial racks filled with more blue drums, extending into the distance under a bright sky. A large, semi-transparent blue graphic element, resembling a technical drawing or blueprint, is overlaid on the bottom left and center of the page. This graphic contains white lines and text, including the product name "Roto Z Foodgrade" and "Atlas Copco Lubricants".

Roto Z Foodgrade

Atlas Copco Lubricants

For oil-free Z rotary screw and tooth compressors

Roto Z Foodgrade is a semi-synthetic high-quality lubricant, uniquely tailored to the specific requirements of the Atlas Copco Z-compressors and to the most stringent requirements of the Food & Beverage, Pharmaceutical and packing industry. Its special formulation yields top performance and maximum lifetime of all moving parts. Reliability is safeguarded and equipment availability is maximal.

Roto Z Foodgrade

Atlas Copco Lubricants

Our Z-compressor technology provides you class 0 (ISO 8573-1) compressed air quality and guarantees 0 contamination of your final products at all times. But because national and international regulations specify strict manufacturing standards regarding contamination risk management in this industry, also outside the compressor room, our Roto Z Foodgrade is developed to meet these stringent requirements, allowing for active Critical Control Points management (in an HACCP system) and providing increased customer confidence in the food products' safety.

The Roto Z Foodgrade will therefore give you this peace of mind throughout your entire company, as incidental contact (due to human mistake, spillage, mixing products, ...) with your process will not form any risk for product contamination at all, avoiding high costs due to production losses, product claims, brand damage, product recalls, etc.

Roto Z Foodgrade is cost-effective too: drain intervals are doubled in comparison to conventional Foodgrade certified lubricants combined with the best lubrication properties in order to resist the highest loads in all rotating parts and avoiding wear over its complete lifetime.



Features		Benefits
Excellent anti-wear properties	Roto Z Foodgrade contains proven anti-wear additives to be effective throughout the range of operating conditions.	This load carrying capacity is particularly important because oil-free compressors are driven by gears, requiring oils with anti-wear properties reducing gear teeth and bearing wear.
Thermal stability	Roto Z Foodgrade is thermal stable in severe conditions of load and temperature.	The oil has a high resistance to degradation and sludge formation.
Oxidation resistance	The good oxidation control minimizes the formation of aggressive corrosive acids, deposits and sludge.	This oxidation resistance will reduce your operating costs.
High viscosity index	Oil viscosity remains at a more stable level, even at high temperatures. This means lubricating efficiency is maintained under varying conditions.	Keeps working hard, whatever the conditions, even at high operating temperature. Increases bearing lifetime and reduces general danger in the oil circuit.



Lubricant characteristics

Appearance: Clear liquid

Performance	Method	Unit	Value
Density at 15°C	ISO 3675	kg/dm ³	0,860
Viscosity at 40°C	ASTM D 445	mm ² /s	68
Viscosity index	ASTM D 2270		133
Foam stability	ASTM D 892	ml	0/0/0
Total acid number	ASTM D 974	mg KOH/g	0,18
Rust test	ASTM D 665B		Pass
Pour point	ASTM D 97	°C	-30

These characteristics are typical of current production. Whilst future production will conform to Atlas Copco’s specification, variations in these characteristics may occur. Complies with ISO 6743 /3 /1A class L-DAH

ID Card

Roto Z Foodgrade	
Oil type	Semi-synthetic based oil with tailored additive pack
Service intervals	All conditions 4 000 h < 55 kW 8 000 h > 55 kW Or 2 years (whichever comes first)
Environment	Ambient temperature range at 0°C to 50°C
Equipment	Atlas Copco oil-free screws & tooth
Compatibility	ZR, ZS, ZT, ZA, ZE compressors
Capacity (ID)	5 l plastic can (1630 2057 05) 20 l plastic can (1630 2057 20) 208 l metal drum (1630 2057 29)
Approvals	NSF – H1, Halal and Kosher



NSF Food Safety



atlascopco.com